MANGUERA INCENDIO PVC
MODELO COMBAT F68 14 BAR

Color	RED
Inner Lining	100% PVC
Hose Jacket	High Tenacity Circular Woven Synthetic Yarn
Outside Cover	100% PVC
Temperature	-25°C-+80°C
Elongation Rate:	<5%
Expansion Rate:	<5%
Abrasion Resistance:	>1500cycles
Adhesion Strength:	>25N/25MM

Nominal Size		Working Pressure		Min. Burst Pressure		Weight		Wall Thickness	
inch	mm	psi	bar	psi	bar	lbs/ft	kg/m	inch	
1 - 1/2"	38	250	17	750	51	0.235	0.35	0.083	2.1
2"	52	250	17	750	51	0.316	0.47	0.087	2.2
2 - 1/2"	65	250	17	750	51	0.423	0.63	0.091	2.3

Package Details:

SIZE	PC/CARTON	CARTON SIZE	N.W(KG/PC)	G.W(KG/CTN)
1.5"×25M	1	51 × 48 × 9 cms.	9.8	10.3
2"×25M	1	51 × 48 × 11 cms.	12.5	13.5
2.5"×25M	1	54 × 51 × 13 cms.	15.9	16.9
2.5"×30M	1	55 × 55 × 13 cms.	20.4	21.4

Aplicaciones: Brigadas de Incendio, deshidratación, descarga de agua, drenaje, instalaciones de riego, bombeo de lodos y fertilizantes líquidos, minas, etc.

Las mangueras son populares debido a su resistencia a la abrasión y al uso intensivo.



Soindus Comercial Ltda.
Germán Ebbinghauss Nº 2969 Puente Alto - Santiago - Chile
Dr. Amador Neghme Nº 03639 Galpón 51 La Pintana - Santiago - Chile
(562) 2567 9613
ventas@soindus.cl
www.soindus.cl