MANGUERA PVC/NITRILE
MODELO COMBAT F68 21 BAR

Color	Rojo
Inner Lining	70% Nitrile and 30% PVC
Hose Jacket	High Tenacity Circular Woven Synthetic Yarn
Outside Cover	70% Nitrile and 30% PVC, Ribbed Cover
Temperature	-25°C-+80°C
Length(M)	25 Y 30
Elongation Rate:	<5%
Expansion Rate:	<5%
Abrasion Resistance:	>2000 cycles
Adhesion Strength:	>30N/25MM

Nominal Size		Working Pressure		Min. Burst Pressure		Weight		Wall Thickness	
inch	mm	psi	bar	psi	bar	lbs/ft	kg/m	inch	
1 - 1/2"	38	300	21	900	63	0.235	0.35	0.083	2.1
2"	52	300	21	900	63	0.316	0.47	0.087	2.2
2 - 1/2"	65	300	21	900	63	0.423	0.63	0.091	2.3

Package Details:

SIZE	PC/CARTON	CARTON SIZE	N.W(KG/PC)	G.W(KG/CTN)
1.5"×25M	1	51 × 48 × 9 cms.	10.8	11.8
2"×25M	1	51 × 48 × 11 cms.	13.6	14.6
2.5"×25M	1	54 × 51 × 13 cms.	17.1	18.1

Aplicaciónes: Uso excepcional Brigadas de incendio, deshidratación, descarga de agua, drenaje, instalaciones de riego, bombeo de lodos y fertilizantes líquidos, minas, etc.

Las mangueras son populares debido a su resistencia a la abrasión y al uso intensivo.



Soindus Comercial Ltda.
Germán Ebbinghauss Nº 2969 Puente Alto - Santiago - Chile
Dr. Amador Neghme Nº 03639 Galpón 51 La Pintana - Santiago - Chile
(562) 2567 9613
ventas@soindus.cl
www.soindus.cl